

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007324 A1

(51) International Patent Classification⁷: **B22D 19/16**,
19/00, 21/04, F02F 1/00, F16J 10/04

[GB/US]; 772 Burroughs Street, Plymouth, MI 48170
(US).

(21) International Application Number:
PCT/AU2004/000949

(74) Agent: **COLLISON & CO**; 117 King William Street,
Adelaide, S.A. 5000 (AU).

(22) International Filing Date: 15 July 2004 (15.07.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003903648 16 July 2003 (16.07.2003) AU

(71) Applicant (*for all designated States except US*): **CASTAL-
LOY MANUFACTURING PTY LTD** [AU/AU]; 76
Mooringe Avenue, North Plympton, SA 5037 (AU).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **BEND, Robert, J.**

[Continued on next page]

(54) Title: CYLINDER LINER IMPROVEMENTS



(57) Abstract: An engine block mold, including at least one barrel slab core (10), the or each barrel slab core (10) including a slab portion (12), and at least one barrel portion (14) adapted to receive a cylinder liner (1), wherein the barrel portion (14) of the or each barrel slab core (10) has an outer diametral taper along at least a portion of its length, and the or each liner (1) has a substantially matching internal diametral taper along at least a portion of its length. Inserting the or each slab barrel core (10) with the or each liner (1) disposed upon it, into a substantially completed mold casing, filling the mold, and then machining the cylinder liners (1) so that they have a substantially constant internal diameter along their length.

WO 2005/007324 A1

BEST AVAILABLE COPY



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

BEST AVAILABLE COPY